

Lagerliste Stahl unbehandelt roh / Stahl schwarz

Flachstahl
S 235 JR
HL= ca. 6000mm

Abmessung	Kg/m	Abmessung	Kg/m	Abmessung	Kg/m
10x5	0,39	40x8	2,51	80x12	7,54
12x5	0,47	40x10	3,14	80x15	9,42
12x6	0,56	40x12	3,77	80x20	12,60
16x5	0,62	40x15	4,71	90x6	4,24
16x6	0,75	40x20	6,28	100x5	3,93
16x8	1,00	50x5	1,96	100x6	4,71
16x10	1,26	50x6	2,36	100x8	6,28
20x5	0,78	50x8	3,14	100x10	7,85
20x6	0,94	50x10	3,93	100x12	9,42
20x8	1,26	50x12	4,71	100x15	11,80
20x10	1,57	50x15	5,89	100x20	15,70
25x5	0,98	50x20	7,85	120x8	7,54
25x6	1,18	60x5	2,36	120x10	9,42
25x8	1,57	60x6	2,83	120x12	11,30
25x10	1,96	60x8	3,77	120x15	14,10
25x12	2,36	60x10	4,71	120x20	18,80
30x5	1,18	60x12	5,65	140x8	8,79
30x6	1,41	60x15	7,07	140x10	11,00
30x8	1,88	60x20	9,42	140x15	16,50
30x10	2,36	70x5	2,75	140x20	22,00
30x12	2,83	70x6	3,30	150x8	9,42
30x15	3,53	70x8	4,40	150x10	11,80
30x20	4,71	70x10	5,50	150x12	14,10
35x5	1,37	70x15	8,24	150x15	17,70
35x6	1,65	80x5	3,14	150x20	23,60
35x8	2,20	80x6	3,77	150x30	35,30
40x5	1,57	80x8	5,02		
40x6	1,88	80x10	6,28		

Ansprechpartner

Herr Petersen
04321/569-118
petersen@daehmlow.de

Herr Katins
04321/569-119
katins@daehmlow.de

Alle Angaben in mm
Alle Angaben ohne Gewähr

Lagerliste Stahl unbehandelt roh / Stahl schwarz

Bandstahl in Stäben S 235 JR HL= ca. 6000mm

Abmessung	Kg/m	Abmessung	Kg/m
10x3	0,23	50x3	1,18
10x4	0,31	50x4	1,57
12x3	0,28	60x3	1,41
16x3	0,37	60x4	1,88
16x4	0,50	80x3	1,88
20x3	0,47	80x4	2,51
20x4	0,62	100x3	2,35
25x3	0,58	100x4	3,14
25x4	0,78	120x3	2,82
30x2	0,47	120x4	3,76
30x3	0,70	120x5	4,71
30x4	0,94	120x6	5,64
40x3	0,94	150x4	4,71
40x4	1,26		

Breitflachstahl S 235 JR HL= ca. 6000mm

Abmessung	Kg/m	Abmessung	Kg/m
150x5	5,87	200x12	19,20
150x6	7,02	200x15	24,00
160x8	10,20	200x20	32,00
160x10	12,80	200x30	48,00
160x12	15,40	220x10	17,60
160x15	19,20	240x10	19,20
160x20	25,60	250x8	16,00
180x8	11,50	250x10	20,00
180x10	14,40	250x12	24,00
180x12	17,30	250x15	30,00
180x15	21,60	250x20	40,00
180x20	28,80	300x10	24,00
200x5	8,00	300x12	28,80
200x6	9,60	300x15	36,00
200x8	12,80	300x20	48,00
200x10	16,00		

Vierkantstahl S 235 JR HL= ca. 6000mm

Abmessung	Kg/m
6	0,28
8	0,50
10	0,78
12	1,13
14	1,54
15	1,77
16	2,01
20	3,14
25	4,91
30	7,07

Ansprechpartner

Lagerliste Stahl unbehandelt roh / Stahl schwarz

Winkelstahl S 235 JR HL= ca. 6000mm

Gleichschenklig		ungleichschenklig	
Abmessung	Kg/m	Abmessung	Kg/m
15x2	0,44	30x20x3	1,11
20x3	0,88	30x20x4	1,45
20x4	1,14	40x20x3	1,35
25x3	1,12	40x20x4	1,77
25x4	1,45	45x30x5	2,77
30x3	1,36	50x30x5	2,96
30x4	1,78	60x30x5	3,37
30x5	2,18	60x40x5	3,76
35x4	2,10	75x50x5	4,74
35x5	2,57	80x40x6	5,41
40x4	2,42	100x50x6	6,85
40x5	2,97	100x65x7	8,77
40x6	3,52	120x80x8	12,20
45x5	3,38	120x80x10	15,00
50x5	3,77	150x75x9	15,30
50x6	4,47	150x100x10	19,00
50x8	5,82	150x100x12	22,60
60x6	5,42	200x100x10	23,00
60x8	7,09		
65x7	6,83		
70x7	7,38		
80x8	9,66		
100x10	15,10		
140x13	27,50		
160x15	36,20		
180x18	48,60		

Quadratrohre S 235 JR HL= ca. 6000mm

Abmessung	Kg/m
15x1,5	0,63
20x2,0	1,12
20x3,0	1,60
25x2,0	1,44
25x3,0	2,07
30x2,0	1,75
30x3,0	2,39
34x2,0	2,00
35x2,0	2,07
40x2,0	2,38
40x3,0	3,33
40x4,0	4,25
45x2,0	2,69
50x2,0	3,01
50x3,0	4,28
50x4,0	5,51
50x5,0	6,90
60x2,0	3,64
60x3,0	5,22
60x4,0	6,76
60x5,0	8,13
70x3,0	6,16
70x4,0	8,02
80x3,0	7,10
80x4,0	9,28
80x5,0	11,30
90x4,0	10,50
100x3,0	8,99
100x4,0	11,90
100x5,0	14,40
120x4,0	14,40

Ansprechpartner

Herr Petersen
04321/569-118
petersen@daehmlow.de

Herr Katins
04321/569-119
katins@daehmlow.de

Alle Angaben in mm
Alle Angaben ohne Gewähr

Lagerliste Stahl unbehandelt roh / Stahl schwarz

**Rechteckrohre
S 235 JR
HL= ca. 6000mm**

Abmessung	Kg/m
25x15x1,5	0,87
30x15x2,0	1,28
30x20x2,0	1,44
30x20x3,0	2,07
40x20x2,0	1,75
40x20x3,0	2,39
40x30x2,0	2,07
40x30x3,0	2,86
50x20x2,0	2,05
50x25x2,0	2,22
50x30x2,0	2,38
50x30x3,0	3,33
50x40x2,0	2,69
55x34x2,0	2,66
60x20x2,0	2,38
60x30x2,0	2,69
60x30x3,0	3,80
60x40x2,0	3,01
60x40x3,0	4,28
60x40x4,0	5,51
80x40x2,0	3,64
80x40x3,0	5,22
80x40x4,0	6,76
80x50x3,0	5,69
80x60x3,0	6,16
80x60x4,0	8,02
100x40x2,0	4,26
100x50x3,0	6,63
100x50x4,0	8,65
100x60x3,0	7,10
100x60x4,0	9,28
120x60x3,0	8,04
120x60x4,0	10,50

**Rundstahl
S 235 JR
HL= ca. 6000mm**

Abmessung	Kg/m
6	0,22
8	0,39
10	0,61
12	0,88
14	1,21
15	1,39
16	1,58
18	2,00
20	2,47
22	2,98
25	3,85
30	5,55

**T-Stahl
S 235 JR
HL= ca. 6000mm**

Abmessung	Kg/m
20x20x3	0,88
25x25x3,5	1,29
30x30x4	1,77
35x35x4,5	2,33
40x40x5	2,96
50x50x6	4,44
60x60x7	6,23
70x70x8	8,32
80x80x9	10,7
100x100x11	16,4

Ansprechpartner

Lagerliste Stahl unbehandelt roh / Stahl schwarz

U-Stahl S 235 JR

Stabstahl HL= ca. 6000mm	
Abmessung	Kg/m
40x35x5	5,02
40x20x5	2,96
50x38x5	5,76
50x25x5	3,98
60x30x6	5,22
65x42x6	7,30

Formstahl	
Abmessung	Kg/m
80x45x6	8,90
100x50x6	10,90
120x55x7	13,70
140x60x7	16,40
160x65x7,5	19,30
180x70x8	22,50
200x75x8,5	26,00
220x80x9	30,00
240x85x9,5	34,00

Breitflanschträger S 235 JR

IPE, mittelbreit	
Abmessung	Kg/m
80 (80x46x3,8)	6,20
100 (100x55x4,1)	8,30
120 (120x64x4,4)	10,70
140 (140x73x4,7)	13,20
160 (160x82x5,0)	16,20
180 (180x91x5,3)	19,30
200 (200x100x5,6)	23,00
220 (220x110x5,9)	26,90
240 (240x120x6,2)	31,50

HEA	
Abmessung	Kg/m
100 (96x100x5)	17,10
120 (114x120x5)	20,40
140 (133x140x5,5)	25,30
160 (152x160x6)	31,20
180 (171x180x6)	36,40
200 (190x200x6,5)	43,00

HEB	
Abmessung	Kg/m
100 (100x100x6)	20,90
120 (120x120x6,5)	27,40
140 (140x140x7)	34,50
160 (160x160x8)	43,70
180 (180x180x8,5)	52,50
200 (200x200x9)	63,00
220 (220x220x9,5)	73,00
240 (240x240x10)	85,00

Ansprechpartner

Herr Petersen
04321/569-118
petersen@daehmlow.de

Herr Katins
04321/569-119
katins@daehmlow.de

Alle Angaben in mm
Alle Angaben ohne Gewähr

Lagerliste Profile unbehandelt roh / Stahl schwarz

Gewinderohre
S 195 T / S 235 JRH
HL= ca. 6030mm

Abmessung	Kg/m
¼" (13,5x2,35)	0,65
3/8" (17,2x2,35)	0,85
½" (21,3x2,65)	1,22
¾" (26,9x2,65)	1,58
1" (33,7x3,25)	2,44
1 ¼" (42,4x3,25)	3,14
1 ½" (48,3x3,25)	3,61
2" (60,3x3,65)	5,10

Siederohr nahtl.
P 235 TR1/2
HL= ca. 6000mm

Abmessung	Kg/m
38,0x2,6	2,27
51,0x2,6	3,10
70,0x2,9	4,80
82,5x3,2	6,26
101,6x3,6	8,70
127,0x4,0	12,10

Konstruktionsrohre
S 235 JR
HL= ca. 6030mm

Abmessung	Kg/m
½" (21,3x2,0)	0,95
¾" (26,9x2,0)	1,22
1" (33,7x2,5)	1,91
1 ¼" (42,4x2,5)	2,47
1 ½" (48,3x2,5)	2,84
2" (60,3x2,5)	3,55

Siederohr geschw.
P 235 TR1/2
HL= ca. 6030mm

Abmessung	Kg/m
76,1x2,6	4,71
88,9x2,9	6,15
108,0x2,9	7,52
114,3x3,2	8,77

Stahlhohlprofil geschw.
S 235 JR
HL= ca. 6030mm

Abmessung	Kg/m
139,7x4,0	13,40
159,0x4,5	17,10
168,3x4,5	18,20
219,1x6,3	33,10

Ansprechpartner