

Lagerliste Stahl Stahl verzinkt

Flachstahl S 235 JR feuerverzinkt HL= ca. 6000mm

Abmessung	Kg/m	Abmessung	Kg/m
20x5	0,83	50x6	2,50
30x3	0,75	50x8	3,33
30x4	1,00	50x10	4,17
30x5	1,25	60x5	2,50
30x6	1,49	60x6	3,00
30x8	1,99	60x8	4,00
40x4	1,34	60x10	4,99
40x5	1,66	80x8	5,32
40x6	1,99	80x10	6,66
40x8	2,66	100x6	4,99
40x10	3,34	100x8	6,66
50x5	2,08	100x10	8,32

Winkelstahl S 235 JR feuerverzinkt HL= ca. 6000mm

gleichschenkelig		ungleichschenkelig	
Abmessung	Kg/m	Abmessung	Kg/m
20x3	0,93	40x20x3	1,43
25x3	1,19	40x20x4	1,88
30x3	1,44	50x30x5	3,14
30x4	1,89	60x30x5	3,57
35x4	2,23	60x40x5	3,99
40x4	2,57	80x40x6	5,73
50x5	4,00	100x50x6	7,26
60x6	5,75	150x100x10	20,10
80x8	10,24		
100x10	16,01		

Ansprechpartner

Herr Petersen
04321/569-118
petersen@daehmlow.de

Herr Katins
04321/569-119
katins@daehmlow.de

Alle Angaben in mm
Alle Angaben ohne Gewähr

Lagerliste Stahl Stahl verzinkt

Quadratrohre S 235 JR feuerverzinkt HL= ca. 6000mm

Abmessung	Kg/m
15x1,5	0,70
20x2,0	1,22
25x2,0	1,56
30x2,0	1,90
34,x2,0	2,17
35x2,0	2,24
40x2,0	2,58
40x3,0	3,66
40x4,0	4,70
50x2,0	3,25
50x3,0	4,65
60x2,0	3,93
60x3,0	5,64
60x4,0	7,31
80x3,0	7,61
100x3,0	9,60
100x4,0	12,54

Rechteckrohre S 235 JR feuerverzinkt HL= ca. 6000mm

Abmessung	Kg/m
30x15x2,0	1,39
30x20x2,0	1,56
40x20x2,0	1,90
40x30x2,0	2,24
50x25x2,0	2,41
50x30x2,0	2,58
60x30x2,0	2,92
60x40x2,0	3,25
60x40x3,0	4,65
80x40x2,0	3,93
80x40x3,0	5,64
100x50x3,0	7,12

U-Stahl S 235 JR feuerverzinkt

Stabstahl HL= ca. 6000mm

Abmessung	Kg/m
40x35x5	5,32
50x38x5	6,11
65x42x6	7,74

Formstahl HL= ca. 6150mm

Abmessung	Kg/m
80	9,43
100	11,55
120	14,52
140	17,38
160	20,46

Rundstahl S 235 JR feuerverzinkt HL= ca. 6000mm

Abmessung	Kg/m
8	0,42
10	0,65
12	0,94
16	1,67

Ansprechpartner

Lagerliste Stahl Stahl verzinkt

U-Bordwandstahl S 235 JR verz. HL= ca. 6000mm

Abmessung	Kg/m
20x20x1,5	0,71
21x21x1,5	0,73
23x23x1,5	0,82
25x25x1,5	0,90
28x28x1,5	1,00
31x28x1,5	1,02

T-Stahl S 235 JR feuerverzinkt HL= ca. 6000mm

Abmessung	Kg/m
30x4	1,88
40x5	3,14
50x6	4,71
60x7	6,60

Hydraulikrohr verz. HL= ca. 6000mm

Abmessung	Kg/m
6,0x1,0	0,12
8,0x1,0	0,17
10,0x1,0	0,22
12,0x1,5	0,38
15,0x1,5	0,49

Gewinderohr verz. geschw. EN 10255 o/ohne HL= ca. 6000mm

Abmessung	Kg/m
¼" (13,5x2,35)	0,67
⅜" (17,2x2,35)	0,89
½" (21,3x2,65)	1,27
¾" (26,9x2,65)	1,65
1" (33,7x3,25)	2,55
1 ¼" (42,4x3,25)	3,28
1 ½" (48,3x3,25)	3,77
2" (60,3x3,65)	5,33
2 ½" (76,1x3,65)	6,80
3" (88,9x4,05)	8,80

geschw. EN 10255 m/mit HL= ca. 6000mm

Abmessung	Kg/m
2 ½" (76,1x3,65)	6,80
3" (88,9x4,05)	8,80

Dampfrohr verz. geschw. EN 10255 o/ohne HL= ca. 6000

Abmessung	Kg/m
1 ¼" (42,4x4,05)	3,89

Planrohr verz. HL= ca. 6000mm

Abmessung	Kg/m
60x1,5	2,33

Ansprechpartner